

REMARKS

It is believed that no fees are due for filing this Supplemental Amendment and Response.

In the event that a telephone conversation would further prosecution and/or expedite allowance, the Examiner is invited to contact the undersigned attorney at (760) 458-1863.

Respectfully Submitted,

By: 

Mark H. Snyder, Esq.  
375 Walnut Avenue  
Unit E  
Carlsbad, CA 92008  
(760) 458-1863

Date: 4 March 2003

Version With Markings To Show Changes Made

516/1. (Once Amended) A device for a moving vehicle having an  
[protecting the] interior seat, seat back and foot well [of a  
moving vehicle] for protecting said interior seat, seat back and  
foot well from being soiled by a child in a safety seat,  
5 comprising:

B1  
a mat having a perimeter and having a conformal surface for  
placement between a safety seat having a base and a lateral  
confinement, and said seat of the vehicle, said mat having a  
10 lateral dimension and a longitudinal dimension, wherein said mat  
lateral dimension extends beyond the lateral confinement of said  
safety seat and has a flange outwardly extending at least 1 inch  
from said conformal surface and around at least a portion of the  
perimeter of said mat to define a containment area for  
15 containment of liquid spills within said mat, and said mat  
longitudinal dimension further extends beyond the base of said  
safety seat and into said foot well.

Version With Markings To Show Changes Made

*Sec 11* 11. (Once Amended) A device for a moving vehicle having an  
[protecting the] interior seat, seat back and foot well [of a  
moving vehicle] for protecting said interior seat, seat back and  
foot well from being soiled by a child in a safety seat,  
5 comprising:

*B2* a mat having a perimeter and having a conformal surface for  
placement between a safety seat having a base and a lateral  
confinement, and the seat of a vehicle, said mat having a lateral  
10 dimension and a longitudinal dimension, wherein said mat lateral  
dimension extends beyond the lateral confinement of said safety  
seat at least 2 inches, and has a flange extending outwardly from  
said mat surfaces at least 1 inch from said mat conformal  
surface, said flange extending around the perimeter of said mat  
15 to define a containment area for containment of liquid spills  
within said mat, said mat also contains a pass-through for a  
safety belt that maintains the integrity of said containment area  
for containment of liquid spills within said mat.

Version With Markings To Show Changes Made

~~Sub 17. (Once Amended) A device for a moving vehicle having an [protecting the] interior seat, seat back and foot well, said foot well having horizontal and vertical surfaces [of the foot well of a moving vehicle], for protecting said interior seat, seat back, and foot well surfaces from being soiled by a child in a safety seat, comprising:~~

B3  
~~a mat having a perimeter and having a conformal surface for placement between a safety seat having a base and a lateral confinement, and the seat of a vehicle, said mat having a flange extending outwardly at least 1 inch from said mat conformal surface, said flange extending around at least a portion of the perimeter of said mat to define a containment area for containment of liquid spills within said mat, and said conformal surface of said mat includes a horizontal portion that conforms to said seat, a vertical portion that conforms to said vertical foot well surface, and a horizontal portion that conforms to said horizontal foot well surface.~~